Material Safety Data Sheet

\$44 SILICONE SEAL



PHYSICAL DATA:

This product is manufactured from a silicon compound designed for applications where fire resistance may be required. The finished product is supplied with an acrylic adhesive (solvent based, resin modified) applied to the back for the purpose of installing the product onto a door frame.

FIRE HAZARD:

This product is a crosslinked sillicon elastomer that will burn with a lazy smoldering type flame. The finished product with adhesive does not present a fire hazard.

FIREFIGHTING TECHNIQUES:

As in any fire, prevent human exposure to fire, smoke, fumes, or products of combustion. Evacuate nonessential personnel from the fire area. Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Use standard fire fighting techniques to extinguish fires involving this material: Use water fog/spray, dry chemical or carbon dioxide.

TOXICITY DATA:

There is no toxicity hazard under normal conditions of use. The adhesive may cause an adhesive-typical odor in very poorly ventilated rooms in individual cases.

HEALTH HAZARD DATA:

This product may contain hazardous ingredients; harmful effects are unlikely under conditions of normal use. Observe proper industrial hygiene, especially wash hands when finished working.

EFFECTS OF EXPOSURE:


None under normal conditions of use. This product is impervious to fungus and mildew: will not deteriorate under normal exposure.

STORAGE & DISPOSAL:

There are no specific handling instructions. Always store at room temperature and keep away from heat sources. When disposing, if possible, recycle; otherwise disposal should be in accordance with local, state or federal legislation. Bury in an authorized landfill site or incinerate under approved controlled conditions.

SPILL PROCEDURES:

Sweep up any cut-offs from product and store in suitable container for disposal.



www.pemko.com

Memphis, TN USA
P.O. Box 18966
Memphis, TN 38181
P: 800.824.3018
F: 800.243.3656